LUXURY LAKES ICE CREAM

# ICE CREAM FREEZER OFFER 2022

IN PARTNERSHIP WITH AHT COOLING SYSTEMS SUPERMARKET (UK) LTD

The Old Dairy · Gilthwaiterigg Lane · Kendal · LA9 6NT · Cumbria

01539 721 211 · info@lakesicecream.com · www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

AHT a member of DAIKIN group

# AHT Rio S G CSGW

**Key Benefits:**

- Excellent product visibility
- Ready to plug in
- Easy to move
- Environmentally friendly
- Bespoke branding
- Very simple maintenance
- Adjustable thermostat

- Rio S 68 Baskets
- Rio S 100 Baskets
- Rio S 125 Baskets
- Rio S 150 Baskets
- Rio S 175 Baskets

68 · 00 · 125 A→G D

150 · 175 A→G E

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 35° C and a maximum of 70% humidity (Class 7).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

| AHT Rio S | 68 G CSGW | 100 G CSGW | 125 G CSGW | 150 G CSGW | 175 G CSGW | |
|---|---|---|---|---|---|---|
| **Dimensions** | | | | | | |
| Gross content | 141 | 252 | 339 | 450 | 542 | Liter |
| Net content | 102 | 190 | 258 | 368 | 444 | Liter |
| Total display area (TDA) | 0,25 | 0,41 | 0,54 | 0,67 | 0,79 | m2 |
| Length outside / inside | 680 / 530 | 1000 / 850 | 1250 / 1100 | 1500 / 1350 | 1750 / 1600 | mm |
| Depth outside / inside | 650 / 500 | 650 / 500 | 650 / 500 | 650 / 500 | 650 / 500 | mm |
| Height outside front / rear | 769 / 883 | 769 / 883 | 769 / 883 | 883 / 883 | 883 / 883 | mm |
| Stacking height front / rear | 530 / 570 | 530 / 570 | 530 / 570 | 610 / 610 | 610 / 610 | mm |
| Net weight | 51 | 69 | 73 | 77 | 88 | kg |
| Gross weight | 54 | 75 | 80 | 84 | 95 | kg |
| **Operation** | | | | | | |
| Ambient temperature (min ... max) | 16 ... 35 | | | | | °C |
| Ambient humidity (RH) (min ... max) | 80 ... 75 | | | | | % |
| Recommended temperature(s) | | | | | | |
| For optimised food storage | -18 | | | | | °C |
| Sound pressure in 1 m distance | 39 | | | | | dB(A) |
| Blowing agent | R-601 (HC) GWP 5 | | | | | |
| **Electrical supply** | | | | | | |
| Nominal voltage / frequency | 220-240 / 50 | | | | | V / Hz |
| Nominal power max. acc. EN 60335-2-89240 | | 280 | 300 | 300 | 320 | |
| Nominal current max. acc. EN 60335-2-89 | | 2,1 | 2,5 | 2,8 | A | |
| Fuse protection | RCBO, 30mA, C10 | | | | | |
| Length of power supply cord | 1750 | | | | | mm |
| **Light source parameters** | | | | | | |
| Type of light source | LED | | | | | |
| Energy efficiency class light source | F | | | | | |
| Nominal power light max. | 8 | 11 | | | | W |
| **Energy consumption** | | | | | | |
| Daily energy consumption* Edaily | 1,36 | 1,87 | 2,51 | 2,37 | 3,02 | kWh/24h |
| Annual energy consumption AE | 497,82 | 681,27 | 914,53 | 864,54 | 1102,15 | kWh/a |
| **HVAC** | | | | | | |
| Rejected heat capacity* | 57 | 78 | 104 | 99 | 126 | W |
| Dehumidification* | 0 | Liter/24h | | | | |
| **Refrigeration system** | | | | | | |
| Refrigerant type | R-290 (HC) GWP3 | | | | | |
| Refrigerant charge max. | 0,050 | 0,060 | 0,070 | 0,075 | 0,080 | kg |
| Max. allowable operating pressure | 30 | bar | | | | |
| General | | | | | | |
| minimum duration of the guarantee offered by the supplier | | | | | | |

AHT
a member of DAIKIN group

The Old Dairy · Gilthwaiterigg Lane · Kendal · LA9 6NT · Cumbria
01539 721 211 · info@lakesicecream.com · www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# Why purchase the AHT Rio S range when it comes to Impulse Display Chests?

- Very low energy consumption
- Galvanized steel inner liner, paired white so more robust than aluminium and also won't corrode.
- NO or very little icing in our cabinets (100% tight - no silicone joints in the 4 angles inside the cabinet)
- Very solid glass lids with frames moulded directly on the glass in one piece
  (no assembly - impossible to rip off the frame and the handle) Avoid Investment in new sets of glass lids for existing freezers
- The frame of our cabinet is in one piece, It is directly moulded on the cabinet during production (no assembly)
- The frame of our cabinet is very solid (ABS)
- Solid bottom and fixation of the wheels
- All components in the compressor room are placed on a drawer (easy to pull out and give easy access for repair)
- The Rio S is climate class 7, meaning it will work as expected in ambient conditions of up to 35°c and 70% humidity.

AHT
a member of DAIKIN group

The Old Dairy · Gilthwaiterigg Lane · Kendal · LA9 6NT · Cumbria
01539 721 211 · info@lakesicecream.com · www.lakesicecream.com
©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Rio H 68 Eutectic with trolley option

## Key Benefits:

- Excellent product visibility
- Ready to plug in
- Easy to move
- Environmentally friendly
- Bespoke branding
- Very simple maintenance
- Adjustable thermostat

| AHT Rio H Eutectic | | | | |
|---|---|---|---|---|
| **General data** | | | | |
| gross content | Liter | 121 | cu.ft. | 4,27 |
| net content | Liter | 105 | cu.ft. | 3,71 |
| classification acc. to EN 23953 | --- | 7L1 | --- | 7L1 |
| ambient temperature range | °C ... °C | 16 ... 35 | °F ... °F | 61 ... 95 |
| inner temperature range | °C ... °C | -14 ... -23 | °F ... °F | 7 ... -9 |
| sound pressure in 1 m distance | dB(A) | 39 | dB(A) | 39 |
| **Electrical data** | | | | |
| nominal voltage/frequency | V / Hz | 220-240/50 | V / Hz | 220-240/50 |
| nominal power consumption cabinet | W | 240 | W | 240 |
| power consumption illumination | W | no light | W | no light |
| nominal current | A | 2,1 | A | 2,1 |
| fuse protection | A | 16 | A | 16 |
| energy consumption (at 30°C) | kWh/24 h | 1,5 | BTU | 5119 |
| length of power supply cord | mm | 1750 | inch | 68,9 |
| **Refrigeration data** | | | | |
| refrigerant type | --- | R-290 | --- | R-290 |
| refrigerant charge | g | 50 | oz | 1,8 |
| max. operating pressure | bar | 30 | bar | 30 |
| **Physical dimensions** | | | | |
| length outside/inside | mm | 680 / 492 | inch | 26,77 / 19,37 |
| depth outside/inside | mm | 650 / 463 | inch | 25,59 / 18,23 |
| front acces height/height outside | mm | 883 | inch | 34,76 |
| height inside front/rear | mm | 700 | inch | 27,56 |
| stacking height | mm | 630 | inch | 24,8 |
| net weight (excl. packaging, excl. internal accessories) | kg | 53 | lb | 117 |
| gross weight (excl. packaging, excl. internal accessories) | kg | 56 | lb | 123 |

- The Rio H 68 Eutectic is a climate class 7! Whilst you are serving from this beautifully designed eutectic freezer, you have the peace of mind that the refrigeration system on this unit is designed to work in ambient temperatures of up to 35°c and 70% humidity.
- The bespoke trolley has a space to put your own parasol. This will also help protect the freezer from ambient conditions
- Once fully charged for the recommended time, the Rio H 68 Eutectic can be used for up to 6 hours without being plugged in.
- Full vinyl branding can be applied for extra advertising

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 35° C and a maximum of 70% humidity (Class 7).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

AHT
a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Sao Paulo G CSGW (LED)

**Key Benefits:**

- Excellent product visibility
- Ready to plug in
- Easy to move
- Environmentally friendly
- Bespoke branding
- Very simple maintenance
- Adjustable thermostat

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 35° C and a maximum of 70% humidity (Class 7).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

* Please note, underneath the serving area on this unit you can store the same amount of tubs as you display

- 6 Pan • G100
- 10 Pan • G150
- 9 Pan • G125
- 12 Pan • G175

Sao Paulo 100 G CSGW ( LED )
Sao Paulo 125 G CSGW ( LED )
Sao Paulo 150 G CSGW ( LED )
Sao Paulo 175 G CSGW ( LED )

A
G
D

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

| AHT Sao Paulo | G 100 | G 125 | G 150 | G 175 | |
|---|---|---|---|---|---|
| **Dimensions** | | | | | |
| Gross content | 299 | 402 | 504 | 607 | Liter |
| Net content | 241 | 326 | 412 | 497 | Liter |
| Total display area (TDA) | 0,47 | 0,61 | 0,75 | 0,89 | m2 |
| Length outside / inside | 998 / 850 | 1248 / 1100 | 1498 / 1350 | 1748 / 1600 | mm |
| Depth outside / inside | 709 / 560 | 709 / 560 | 709 / 560 | 709 / 560 | mm |
| Height outside front / rear | 883 / 883 | 883 / 883 | 883 / 883 | 883 / 883 | mm |
| Stacking height front / rear | 610 / 610 | 610 / 610 | 610 / 610 | 610 / 610 | mm |
| Net weight | 68 | 78 | 88 | 98 | kg |
| Gross weight | 70 | 80 | 90 | 100 | kg |
| **Operation** | | | | | |
| Ambient temperature (min ... max) | 16 ... 35 | °C | | | |
| Ambient humidity (RH) (min ... max) | 80 ... 75 | % | | | |
| Recommended temperature(s) | | | | | |
| For optimised food storage | -18 | °C | | | |
| Sound pressure in 1 m distance | 39 | dB(A) | | | |
| Blowing agent | R-601 (HC) GWP 5 | | | | |
| **Electrical supply** | | | | | |
| Nominal voltage / frequency | 220-240 / 50 | V / Hz | | | |
| Nominal power max. acc. EN 60335-2-89 | 280 | 280 | - | - | |
| Nominal current max. acc. EN 60335-2-89 | 2,3 | 2,3 | | A | |
| Fuse protection | RCBO, 30mA, C10 | | | | |
| Length of power supply cord | 1750 | mm | | | |
| **Light source parameters** | | | | | |
| Type of light source | LED | | | | |
| Energy efficiency class light source | F | | | | |
| Nominal power light max. | 8 | 11 | - | - | W |
| **Energy consumption** | | | | | |
| Daily energy consumption* Edaily | 1,81 | 2,01 | 2,51 | - | kWh/24h |
| Annual energy consumption AE | 660,75 | 733,29 | - | - | kWh/a |
| **HVAC** | | | | | |
| Rejected heat capacity* | 75 | 84 | - | - | W |
| Dehumidification* | 0 | Liter/24h | | | |
| **Refrigeration system** | | | | | |
| Refrigerant type | R-290 (HC) GWP3 | | | | |
| Refrigerant charge max. | 0,060 | 0,070 | - | - | kg |
| Max. allowable operating pressure | 30 | bar | | | |
| General | | | | | |
| minimum duration of the guarantee offered by the supplier | | | | | |

AHT
a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint TG3 Countertop Scoop

## FLEXIBLE SCOOPING, ANYWHERE

| AHT Coolpoint TG3 Countertop Scooping Model | TG3 | |
|---|---|---|
| **Technical characteristics** | | |
| Net capacity | 15 | Litres |
| Ambient temperature | 16°C to 25°C | °C |
| Maximum ambient humidity | 60 | % |
| Product temperature setting range | -16°C to -20°C | °C |
| **Electrical specifications** | | |
| Rated voltage / frequency | 230 V/ 50 Hz | V/Hz |
| Consumption (at 25 °C) | 2.9 | kWh/24 h |
| **Refrigeration characteristics** | | |
| Refrigerant | R134a | |
| **Dimensions** | | |
| Width outside | 700 | mm |
| Height outside | 675 | mm |
| Max. depth outside | 515 | mm |
| **Weight** | | |
| Net weight (excluding packaging) | 34 | kg |

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 25° C and a maximum of 60% humidity (Class 3).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

**Key Benefits:**

- Compact Design
- Perfect for small retail premises
- Large branding surface
- Low noise level
- Very easy to clean
- Stainless steel Napoli pans not included

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint Counter Top 50 & 100 CF

## SMALL FORM FACTOR, EXCELLENT DISPLAY

100 CF

50 CF

**Key Benefits:**

- Stylish design
- Low running costs
- Full LED illumination
- Light canopy on 100CF
- Adjustable shelving
- Removable gaskets
- Lock
- Electronic controller
- Adjustable feet

| AHT Coolpoint 50 & 100 CF | 50 CF | 100 CF | |
|---|---|---|---|
| **Technical characteristics** | | | |
| Net capacity | 49 | 66 | L |
| Climate Class | 4 | 4 | |
| Ambient temperature | 16°C to 30°C | 16°C to 30°C °C | |
| Maximum ambient humidity | 70 % | | |
| Product temperature setting range | -18° to -22°C | -18° to -22°C °C | |
| **Electrical Specifications** | | | |
| Rated voltage / frequency | 230V/50Hz | 230V/50Hz | V/Hz |
| Consumption (at 25 °C) | 1.7 | 2.25 | kWh/24 h |
| **Refrigeration characteristics** | | | |
| Refrigerant | R-290 | R-290 | Gas |
| **Dimensions** | | | |
| Width outside | 480 | 530 | mm |
| Cabinet Height outside (excluding canopy) | 657 | 865 | mm |
| Max. depth outside | 464 | 480 | mm |
| **Weight** | | | |
| Net weight (excluding packaging) | 40 | 46 | kg |

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 25° C and a maximum of 60% humidity (Class 3).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Boston 210 CNFX Scooping Freezer

## MAXIMUM DISPLAY & STORAGE
## PLUS UNBEATABLE VALUE FOR MONEY

Key Benefits:

- Excellent product visibility
- Ready to plug in
- Easy to move
- Environmentally friendly
- Bespoke branding
- Very simple maintenance
- Adjustable thermostat
- Great for point of sale

Dimensions:
Sizes: 2100mm



- 22 Pan Display

**Running out of space for cones, tubs and sprinkles?
Why not use the newly launched Boston Top Shelf!
A new accessory to our range, available soon!**

| AHT Boston 210 | Boston 210 | |
|---|---|---|
| **Technical characteristics** | | |
| Gross capacity | 1340 | L |
| Net capacity according to EN23953 | 710 | L |
| Classification according to EN23953 | 3L1 | |
| Ambient temperature | 16°C to 25°C °C | |
| Maximum ambient humidity | 60 % | |
| Product temperature setting range | -12° to -23°C °C | |
| **Electrical Specifications** | | |
| Rated voltage / frequency | 230V/50Hz | V/Hz |
| Consumption (at 25 °C) | 5.1 | kWh/24 h |
| **Refrigeration characteristics** | | |
| Refrigerant | R-290 | Gas |
| **Dimensions** | | |
| Width outside | 2102 | mm |
| Cabinet Height outside (excluding canopy) | 1178 | mm |
| Max. depth outside | 854 | mm |
| **Weight** | | |
| Net weight (excluding packaging) | 161 | kg |
| Gross weight (with packaging) | 180 | kg |

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 25° C and a maximum of 60% humidity (Class 3).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

AHT
a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com
©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint PF85 Can Freezer

## PERFECT FOR PACKAGED ICE CREAM & LOLLIES

**Key Benefits:**

- Space for branding
- Ready to plug in
- Easy to move
- Environmentally friendly
- Bespoke branding
- Very simple maintenance

| AHT Coolpoint PF Can Freezer | 85 | |
|---|---|---|
| Net capacity according to EN 23953 | 72 | L |
| Classification according to EN 23953 | 3L1 | |
| Ambient temperature | 16°C to 25°C | °C |
| Maximum ambient humidity | 60 | % |
| Product temperature setting range | -12°C to -22°C | °C |
| **Electrical specifications** | | |
| Rated voltage / frequency | 230 V/ 50 Hz | V/Hz |
| Consumption (at 25 °C) | 2 | kWh/24 h |
| **Refrigeration characteristics** | | |
| Refrigerant | R600a | |
| **Dimensions** | | |
| Width outside | 570 | mm |
| Height outside | 830 | mm |
| Max. depth outside | 570 | mm |
| **Weight** | | |
| Net weight (excluding packaging) | 30 | kg |

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 25° C and a maximum of 60% humidity (Class 3).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com
©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint 309F

## RELIABILITY & EXCELLENT PRODUCT VISIBILITY

Key Benefits:

- Ventilated freezer
- Auto defrost
- Ready to plug in
- Self closing door
- Reversable door
- 5 adjustable shelves
- Environmentally friendly
- Bespoke branding
- Very simple maintenance
- Product lighting

| AHT Coolpoint 309 F | 309F F | |
|---|---|---|
| Net capacity according to EN 23953 | 351 | L |
| Classification according to EN 23953 | 3L1 | |
| Ambient temperature | 16°C to 25°C | °C |
| Maximum ambient humidity | 60 | % |
| Product temperature setting range | -16°C to -25°C | °C |
| **Electrical Specifications** | | |
| 220-240 V/ 50 Hz | V/Hz | |
| Consumption (at 25 °C) | 1 | kWh/24 h |
| **Refrigeration characteristics** | | |
| Refrigerant | R-290 | |
| **Dimensions** | | |
| Width outside | 595 | mm |
| Height outside | 1850 | mm |
| Max. depth outside | 595 | mm |
| **Weight** | | |
| Net weight (excluding packaging) | 87 | kg |

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint KF870

## RELIABILITY & EXCELLENT PRODUCT VISIBILITY

**Key Benefits:**

- Ventilated freezer
- Autodefrost
- Ready to plugin
- Adjustable shelves
- Environmentally friendly
- Bespoke branding
- Very simple maintenance
- Product lighting

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

| AHT KF870 | KF870 |
|---|---|
| Numbers per. 40' HC container | 48 |
| Temperature range, °C | -12 to -24 |
| Climate class | 4 |
| Energy consump. kWh/24h (E24h) | 9,8 |
| Energy consump. kWh/year | 3577 |
| Refrigerant (type/gram) | R404a/375 |
| Cooling Method (static/ventilated) | Ventilated |
| Controller (digital/mechanical) | Digital |
| Length of power cord, meter | / |
| Effect (Watt) | 654 |
| Power input (Volt/Hz) | 220/50 |
| Noise level dB(A) | / |
| Running AMPS | 5 |
| Numbers of shelves | 6 |
| Ajustable shelves | Yes |
| Shelf material | White wire |
| Shelves trim | Price label front |
| Large shelves size (WxD), mm | 524 x 347 |
| Small shelve size (WxD), mm | / |
| Canopy lightsign | Yes |
| Internal light | LED |
| Watt bulb | / |
| LED controlpanel | Yes |
| Door type | Glass |
| Reversible door | No |
| Self closing door | No |
| Handle | Built-in |
| External thermometer | Yes |
| Lock and key | Yes |
| Feets / adjustable feets | 4 |

* FURTHER INFORMATION AVAILABLE ON REQUEST

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 30° C and a maximum of 55% humidity (Class 4).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature. We recommend the use of air conditioning.

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint Slim Freezer

## SLIMLINE GLASS DOOR FREEZER, PERFECT FOR IMPULSE DISPLAY WHERE SPACE IS LIMITED

**AHT Coolpoint Slim Upright Freezer**

Measurements

| | Width | Depth | Height |
|---|---|---|---|
| Outer dimensions (mm) | 400 | 480 | 1870 |
| Inner dimensions (mm) | 280 | 280 | 1273 |
| Packing dimensions (mm) | 860 | 1020 | 2030 |

Colour · White

| | | |
|---|---|---|
| Temperature classification | - 7 ( 35°c-75%) | |
| Temperature Range | ( -18/-25°c) | |
| Voltage | V | 230 |
| Frequency | Hz | 50 |
| Current | A | 2,45 |
| Energy Consumption | W | 0,35 |
| Refrigerant | -R290 | |

CE Certified

This unit will come with an EU plug and a commercially rated 3 Pin UK plug adaptor

Functioning Environment: Our Freezers are designed to work at room temperature between 16°c- 35°c and 70% humidity (Class 7)

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

**KEY FEATURES:**

- Intgerated Door Handle
- Manual Defrost
- LED Light
- Fixed Metal Shelves
- Static Cooling
- Door Self-Closing
- Illuminated Canopy

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy · Gilthwaiterigg Lane · Kendal · LA9 6NT · Cumbria

01539 721 211 · info@lakesicecream.com · www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint KF992 DD

## RELIABILITY & EXCELLENT PRODUCT VISIBILITY

Key Benefits:

- Ventilated freezer
- Digital controller
- Ready to plugin
- Self closing door
- 10 adjustable shelves
- Environmentally friendly
- Shelf 518x439
- Bespoke branding
- Very simple maintenance
- Product lighting
- LED Control Panel

| AHT Coolpoint KF992 DD Freezer Pro | KF991 DD | |
|---|---|---|
| **Technical characteristics** | | |
| Net capacity according to EN 23953 | 810 | L |
| Climate class | 3L1 | |
| Ambient temperature | 16°C to 25°C | ° C |
| Maximum ambient humidity | 60 | % |
| Product temperature setting range | -23°C | °C |
| **Electrical Specifications** | | |
| Rated voltage/frequency | 220-240 V/ 50 Hz | V/Hz |
| Consumption (at 25 °C) | 13.5 | kWh/24 h |
| **Refrigeration characteristics** | | |
| Refrigerant | R-290 | |
| **Dimensions** | | |
| Width outside | 1200 | mm |
| Height outside | 1998 | mm |
| Max. depth outside | 740 | mm |
| **Weight** | | |
| Net weight (excluding packaging) | 214 | kg |

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 30° C and a maximum of 55% humidity (Class 4).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

A to G E

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy · Gilthwaiterigg Lane · Kendal · LA9 6NT · Cumbria
01539 721 211 · info@lakesicecream.com · www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint VGL Scooping Range

## KEY BENEFITS

- LED lighting
- R290 Refrigerant
- Lock
- 4 Castors
- Mechanical Thermostat
- An energy efficient choice
- Climate Class 4
- Temperature Range is -11/-22°c
- Flat galss sliding lids

Canopy Dimensions:
Base - 610mm deep • Top - 184mm deep • Height - 371mm • Width - dependant on model

1 AHT Coolpoint
5 x 5l Scooping Freezer

2 AHT Coolpoint
8 x 5l Scooping Freezer

3 AHT Coolpoint 1
10 x 5l Scooping Freezer

4 AHT Coolpoint
12 x 5l Scooping Freezer

## AHT Coolpoint Scooping Range

Please see below the different size options available

Option 1 - 5 x 5l napoli framework
Option 2 - 8 x 5l napoli framework
Option 3 - 10 x 5l napoli framework
Option 4 - 12 x 5l napoli framework

Average energy consumption over a 24hr period

| | | |
|---|---|---|
| Option 1 | - 5 x 5l napoli framework | - 1.2KW |
| Option 2 | - 8 x 5l napoli framework | - 2KW |
| Option 3 | - 10 x 5l napoli framework | - 2.2KW |
| Option 4 | - 12 x 5l napoli framework | - 2.7KW |

External Dimensions: W X D X H ( In relation to Options above )

Option 1 - 755 x 655 x 910
Option 2 - 1045 x 655 x 910
Option 3 - 1310 x655 x 910
Option 4 - 1540 x 655 x 895

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 30° C and a maximum of 55% humidity (Class 4).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature. We recommend the use of air conditioning.

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

COOLPOINT AHT

AHT
a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint VGS Impulse Chest Freezers

## PERFECT FOR IMPULSE ICE CREAM TUBS

**Key Benefits:**

- Mechanical Thermostat
- Lock and Key Set
- Castors
- Static refrigeration
- Manual Defrost
- Great Product Display

*Baskets with dividers ensure efficient organization of products (optional)*

| AHT VGS Impulse Freezer | VGS 206 | VGS 306 | VGS 406 | VGS 506 | VGS 606 |
|---|---|---|---|---|---|
| Technical Specifications | | | | | |
| Refrigeration system | Static freezing | Static freezing | Static freezing | Static freezing | Static freezing |
| Capacity - Gross/ Net (litres) | 194/149 | 299/240 | 395/312 | 478/382 | 563/454 |
| External dimensions (WxDxH/mm) | 755 x 655 x 910 | 1045 x 655 x 910 | 1310 x655 x 910 | 1540 x 655 x 910 | 1775 x 655 x 910 |
| Internal dimension (WxDxH/mm) | 630 x 530 x 700 | 920 x 530 x 700 | 1185 x 530 x 700 | 1415 x 530 x 700 | 1650 x 530 x 700 |
| Temperatur range (°C) | ÷22 - ÷11 | ÷22 - ÷11 | ÷22 - ÷11 | ÷22 - ÷11 | ÷22 - ÷11 |
| Input power (watt) | 88 | 92 | 108 | 116 | 167 |
| Energy consumption (kWh/24t) | 2,10 | 2,14 | 2,53 | 2,72 | 3,21 |
| Net weight (kg) | 45 | 58 | 66 | 73 | 77 |
| Glass lid | Yes | Yes | Yes | Yes | Yes |
| Frame | Alu | Alu | Alu | Alu | Alu |
| Exterior finish | White | White | White | White | Whitev |
| Interior finish | Alu | Alu | Alu | Alu | Alu |
| Lock | Yes | Yes | Yes | Yes | Yes |
| Feet/Castors | Castors | Castors | Castors | Castors | Castorsv |
| Refrigerant | R290 | R290 | R290 | R290 | R290 |
| Energy class | C | D | D | D | E |
| Basket Configuration | 2 Baskets | 3 Baskets | 4 Baskets | 5 Baskets | 6 Baskets |

Functioning Environment:
Our Freezers are designed to work at room temperature between 16° and 30° C and a maximum of 55% humidity (Class 4).

Beyond those thresholds the cabinets functions may be affected and it will be necessary to check the stores temperature.
We recommend the use of air conditioning.

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

VGS 206

VGS 306

VGS 406

VGS 506

VGS 606

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy · Gilthwaiterigg Lane · Kendal · LA9 6NT · Cumbria
01539 721 211 · info@lakesicecream.com · www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint TL
# Frozen Storage

## RELIABLE, ECONOMICAL STORAGE

**Key Benefits:**

- Storage chest freezer with foamed lid
- Digital temperature readout
- Visual temperature alarm
- Inside light
- Lock

| AHT Coolpoint TL Storage Range | TL 300 | TL 400 | |
|---|---|---|---|
| Net capacity according to EN 23953 | 282 | 464 | L |
| Classification class | 4 | 4 | |
| Ambient temperature | 16°C to 25°C | 16°C to 25°C | °C |
| Maximum ambient humidity | 60 | 60 | % |
| Product temperature setting range | -17°C to -24°C | -17°C to -24°C | °C |
| Electrical Specifications | | | |
| Rated voltage / frequency | 220-240 V/ 50 Hz | 220-240 V/ 50 Hz | V/Hz |
| Consumption (at 25 °C) | 0.92 | 1.21 | kWh/24 h |
| Refrigeration characteristics | | | |
| Refrigerant | R-600a | R-600a | |
| Dimensions | | | |
| Length outside | 1020 | 1560 | mm |
| Height outside | 850 | 850 | mm |
| Max. depth outside | 600 | 600 | mm |
| Weight | | | |
| Net weight (excluding packaging) | 50 | 64 | kg |

Capacity (Net):
Litres: 282| 464 (larger available)

| Table Energy Efficiency Class | | |
|---|---|---|
| Label | EEI from / to | |
| A | 0 | 9.9 |
| B | 10 | 19.9 |
| C | 20 | 34.9 |
| D | 35 | 49.9 |
| E | 50 | 64.9 |
| F | 65 | 79.9 |
| G | 80 | 109.9 |
| H | 110 | |

COOLPOINT AHT

AHT a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AHT Coolpoint Scoop Washer Accessory

## COMPATIBLE WITH ANY FREEZER

Key Benefits:

- Mounting angle bracket 380mm long made from brushed finished stainless steel with 3M VHB double sided tape (as specified)
- Pre-fitted to the 150mm wide back for fixing to a fresh powder coated finish
- Top face 120mm with two holes for Gastronome containers.
- Each bracket comes complete with 2no size 1/9 x 150mm deep
- Gastronome containers made from pressed stainless steel
- The assembly weighs 1.6kg excluding water and scoops, which are not included

AHT
a member of DAIKIN group

The Old Dairy · Gilthwaiterigg Lane · Kendal · LA9 6NT · Cumbria
01539 721 211 · info@lakesicecream.com · www.lakesicecream.com
©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved

# AFTERCARE TROUBLESHOOTING GUIDE. PLEASE KEEP A COPY TO REFER TO AFTER PURCHASE

**Operating your cabinet**

- Do not make any technical changes to your cabinet.
  Otherwise there is a risk of injury of electric shock
- Do not climb onto the lid or on top of the cabinet. There is a risk of injury due to material breakage
- Do not exceed the load line on the cabinet this will impact performance.
  For scooping units all pan displays should be filled to ensure correct operation

**Looking after your cabinet**

- Your unit does not need much maintenance but simple steps will prolong the life of the unit and ensure it works correctly
- Regularly wipe off the outside of the compressor grille with a dry cloth to remove any dust or debris build-up. You can also gently use a vacuum nozzle for this .
  NEVER USE A STEAM OR HIGH PRESSURE CLEANER
- Caution: Before removing the grille, always remove the plug from the power supply.
  All work on the power supply must be performed by suitably qualified staff

## AHT Service Hotline

Call - 01280 826600 (option 2)
AHT Cooling Systems (UK) Ltd
Unit C
Mill Court
Featherstone Road
Wolverton Mill
Milton Keynes
MK12 5EU

**Defrost**

- Ice build-up of 10mm indicates defrosting is required
- Empty the cabinet of all products
- Place a tray under the external drain hole (if the unit has one)
- To speed the process up you can place a container of warm water inside the unit
- Never use sharp implements to scrape as this may damage the unit
- When ice has melted away clean the unit with soap and water (no chemical detergent)
- Ensure the unit is completely dry before switching back on (to avoid ice build up and condensation)

**Cabinet storage**

- Be sure to defrost, clean and dry the unit fully. Leave lids/door open
- Cover the unit with a sheet (to protect against dust & dirt

**Troubleshooting**

- In the unlikely event your unit is not operating to its optimum performance please ensure the following checks have been carried out before contacting the responsible service team.

**Cabinet not running correctly:**

- Check the electrical supply
- Check the thermostat setting
- Check the power supply connection

**Cabinet not at the correct temperature:**

- Check the air grille is not covered and at least 5cm is free around the freezer
- Check the cabinet is not in direct sunlight
- Check the lids/doors have not been left open
- Check the load line has not been exceeded
- Cabinet should be placed on a flat surface
- Site the cabinet away from other sources of heat
- Consider the limits of the climate classification (heat and humidity)
- After transportation please leave the cabinet 4 hours unplugged
- Cabinet will take 2-3 hours to reach temperature
- Keep the lids/doors closed whenever possible

AHT
a member of DAIKIN group

The Old Dairy • Gilthwaiterigg Lane • Kendal • LA9 6NT • Cumbria
01539 721 211 • info@lakesicecream.com • www.lakesicecream.com

©Copyright 2021 English Lakes Ice Cream Ltd. All Rights Reserved